

Printing date 04.12.2017 Version number 12 Revision: 04.12.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: HYBRISEAL 540
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Sealant
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Den Braven France s.a.r.l.

Zone Industrielle du Meux, BP 20114

60880 LE MEUX Cédex

FRANCE

olivier.huss@denbraven.fr

- · Further information obtainable from: Product safety department
- · 1.4 Emergency telephone number: During normal opening times: +33 3 44 91 68 68

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- $\cdot \ Classification \ according \ to \ Regulation \ (EC) \ No \ 1272/2008$

The product is not classified according to the CLP regulation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008 Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · Additional information:

Contains dibutyltin dilaurate, Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous	components:
-------------	-------------

CAS: 2768-02-7 EINECS: 220-449-8

trimethoxyvinylsilane

1-2.5%

Reg.nr.: 01-2119513215-52-xxxx | H332

🌢 Flam. Liq. 3, H226; 🕸 STOT RE 2, H373; 🗘 Acute Tox. 4,

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: No special measures required.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.

(Contd. on page 2)

Printing date 04.12.2017 Version number 12 Revision: 04.12.2017

Trade name: HYBRISEAL 540

· After swallowing: If symptoms persist consult doctor.

(Contd. of page 1)

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up: Pick up mechanically.
- · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility:

Do not store together with oxidising and acidic materials.

- · Further information about storage conditions: Protect from heat and direct sunlight.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

\cdot Ingredients with limit values that require monitoring at the workplace:		
28553-12-0 di-''isononyl'' phthalate (10-25%)		

WEL Long-term value: 5 mg/m³

77-58-7 dibutyltin dilaurate (0.1-1.0%)

WEL Short-term value: 0.2 mg/m³ Long-term value: 0.1 mg/m³ as Sn; Sk

· Additional Occupational Exposure Limit Values for possible hazards during processing:

67-56-1 methanol

WEL	Short-term value: 333 mg/m ³ , 250 ppm
	Long-term value: 266 mg/m³, 200 ppm
	C1-

Sk

(Contd. on page 3)

Printing date 04.12.2017 Version number 12 Revision: 04.12.2017

Trade name: HYBRISEAL 540

(Contd. of page 2)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures: Do not eat, drink, smoke or sniff while working.
- · Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

Filter AX

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves



Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

· Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 60 minutes (Permeation according to EN 374 Part 3: Level 3).

· Eye protection: Safety glasses

CECUTONIA DI			4.0
SECTION 9: Ph	veical and c	rhemical	nronerfies
DECTION 7. III	y sicai aila c	- II CIIII Cai	properties

F-F		
· 9.1 Information on basic physic	cal and chemical properties	
· General Information		
· Appearance:	_	
Form:	Pasty	
Colour: · Odour:	Various colours Characteristic	
	Characteristic	
· Change in condition Initial hoiling point and hoilir	ng range. Undetermined	
Initial boiling point and boiling range: Undetermined.		
· Flash point:	>66 °C	
· Ignition temperature:	420 °C	
· Explosive properties:	Product does not present an explosion hazard.	
· Explosion limits:		
Lower:	0,1 Vol %	
Upper:	0,2 Vol %	
· Vapour pressure:	Not determined.	
· Density at 20 °C:	1,3 g/cm ³	
· Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
· Viscosity:		
Dynamic at 20 °C:	800.000 mPas	
· Solvent content:		
VOC (EC)	4.23 %	
VOC (EC)	57.2 g/l	
· 9.2 Other information	No further relevant information available.	

Printing date 04.12.2017 Version number 12 Revision: 04.12.2017

Trade name: HYBRISEAL 540

(Contd. of page 3)

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx) silicon dioxide (SiO2)

During the crosslinking / polymerization: Methanol

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	· LD/LC50 values relevant for classification:		
2768-02-7	2768-02-7 trimethoxyvinylsilane		
Oral	Oral LD50 7,120 mg/kg (rat)		
Dermal	LD50	3,540 mg/kg (rabbit)	
Inhalative	Inhalative LC50/4 h 16.8 mg/l (rat)		
77-58-7 di	77-58-7 dibutyltin dilaurate		
Oral	LD50	175 mg/kg (rat)	

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eve damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

CD.

Printing date 04.12.2017 Version number 12 Revision: 04.12.2017

Trade name: HYBRISEAL 540

(Contd. of page 4)

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation Smaller quantities can be disposed of with household waste.
- · European waste catalogue

08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION	14. Trong	ant infam	nation
	14: 11(a)(s)	monu muom	IRUUUII

· 14.1 UN-Number · ADR, ADN, IMDG, IATA	Void
· 14.2 UN proper shipping name · ADR, ADN, IMDG, IATA	Void
· 14.3 Transport hazard class(es)	
· ADR, ADN, IMDG, IATA · Class	Void
· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user	Not applicable.
• 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.	
· UN "Model Regulation":	Void

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 20, 52a
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H332 Harmful if inhaled.

 ${
m H373~May}$ cause damage to organs through prolonged or repeated exposure.

- · Department issuing SDS: Product safety department
- · Contact: Mr. Huss
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 6)

Page 6/6

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.12.2017 Version number 12 Revision: 04.12.2017

Trade name: HYBRISEAL 540

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

* Data compared to the previous version altered.

(Contd. of page 5)