

**B&R “A” LACQUER THINNERS
PRODUCT SPECIFICATION &
SAFETY DATA SHEET**

1. IDENTIFICATION

Trade / Commercial Name	A Grade Lacquer Thinners
Synonyms	Cellulose Thinners / Thinners 200
Chemical formula	Formulated chemical
Chemical family	Hydrocarbon solvent, alcohols and ketones
Un No	1263
ERG No	153
Hazchem Code	2x
EAC	60

PROPERTIES	UNITS	TYPICAL VALUES
Boiling Point – 760mm HG	Deg. Celsius	65 – 90°C
Melting Point (pour pt)	Deg. Celsius	Less than –40°C
Vapour pressure (at 40°C)		2 – 400 mm
Vapour density (Air = 1)		2
Distillation Range (IBP°C)		10 = 60 20 = 80 50 = 84 90 = 95 FBP = 170
Density at 20°C	Kg/l	0,8147
Residue on evaporation (100ml)	Mg/kg	Less than 0,01
Flash point	Deg. Celsius	Less than -5°C
Colour	Saybolt	+30

2. COMPOSITION OF INGREDIENTS

Aromatic Solvent	25 - 35	% vol
Alcohol	30 - 40	% vol
Ketones	20 - 30	% vol
BGE	5 - 8	% vol

3. HAZARDS IDENTIFICATION

Identification of the risks

R11 Highly flammable.

R36 Irritating to eyes.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

Particular risks to human beings and the environment

Highly flammable.

Toxic - poisonous

SPECIAL PROTECTION DATA

Ventilation requirements	Area must be well ventilated
Respiratory (in detail)	Air supplied respirator for high concentrations
Eyes	Safety goggles
Gloves	Rubber gloves

4. FIRST AID

HEALTH HAZARD INFORMATION

Emergency overview: clear liquid corrosive to skin and mucous membranes
Medical conditions aggravated by exposure: dermatitis, existing respiratory disease
and existing liver and kidney disease.

Causes	Symptoms	Emergency and first aid procedures
Inhalation (Breathing)	High vapour concentrations may be irritating to the eyes, nose and respiratory tract. May cause headaches, dizziness and nausea. Use with adequate ventilation. Repeated inhalation may cause lung damage. Irritating to mucous membranes and acts as an anesthetic in very high concentrations.	If patient is overcome, remove to fresh air and call a physician. Administer artificial respiration if breathing is irregular or has stopped. Note: do not use mouth to mouth. Use a pocket mask with a one-way valve.
Skin Contact / Absorption	May cause skin irritation and/or dermatitis. Prolonged excessive contact causes defatting and drying out of the skin.	Remove and isolate contaminated clothing and shoes. Avoid spreading material on unaffected skin. Wash well with soap and water. Keep warm and quiet.
Eye Contact	Contact will cause irritation and/or burns. Irritation to eye caused at concentrations greater than 500 ppm.	Flush thoroughly with water for at least 15 minutes, within 1 minute of contact. Hold eyelids open while washing. In severe cases, obtain medical attention.

Ingestion (Swallow)	May cause pulmonary damage or chemical pneumonitis, if aspirated into the lungs. Toxic if swallowed.	If victim is still conscious and not having convulsions, induce vomiting and obtain medical attention promptly. Administer vegetable oil.
Carcinogenicity	NTP – not listed IARC – not listed OSHA – not listed	
Acute over-exposure	If present in high concentrations, vapours cause moderate irritation of eyes and respiratory systems. Effect is temporary.	

5. FIRE FIGHTING MEASURES

Carbon dioxide, foam and dry chemical.

Fire involving Tanks or Bulk Containers: Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Do not get water inside containers. ALWAYS stay away from the ends of tanks.

Cool containers with flooding quantities of water until well after fire is out.

Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.

Isolate spill or leak area immediately for at least 25 to 50 metres (80 to 160 feet) in all directions.

Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate enclosed areas.

Wear positive pressure self-contained breathing apparatus (SCBA).

Wear chemical protective clothing, which is specifically recommended by the manufacturer.

Structural firefighters' protective clothing is recommended for fire situations ONLY; it is not effective in spill situations.

If ROAD OR RAIL TANKER is involved in a fire, ISOLATE for 800 metres (1/2 mile) in all directions, also, consider initial evacuation for 800 metres (1/2 mile) in all directions.

6. HANDLING AND STORAGE

Store between 0 and 28°C.

Keep out of direct sunlight.

Empty containers may retain hazardous residue and explosive vapours.

Keep away from heat, sparks or flame.

Do not cut, puncture, or weld on or near this container.

Follow label warnings until container is thoroughly cleaned or destroyed.

7. ACCIDENTAL RELEASE MEASURES

PRECAUTIONS:

Absorb with fire retardant treated sawdust, diatomaceous earth etc. Shovel up and dispose at an appropriate waste disposal facility.

Restrict access to area.

Provide adequate protective equipment and ventilation.

Remove sources of heat and flame.

Notify occupational and environmental authorities.

SPILL OR LEAK:

Poisonous highly flammable liquid

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Stop leak if you can do it without risk.

Prevent entry into waterways, sewers, basements or confined areas.

Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.

DO NOT GET WATER INSIDE CONTAINERS

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational Exposure Limits Controls

NO EXPOSURE LIMITS ESTABLISHED

The control measures appropriate for a particular worksite depend on how this material is used and on the extent of exposure. The best protection is to enclose operations and/or provide local exhaust ventilation at the site of chemical release. Use a non-sparking, grounded ventilation system separate from other exhaust ventilation systems. Exhaust directly to the outside. Supply sufficient replacement air to make up for air removed. Have a safety shower/eye wash fountain readily available in the immediate work area.

Personal Protection

If engineering controls and work practices are not effective in controlling this material, then wear suitable personal protection equipment, including chemical safety goggles & face shield, boots, impervious gloves, coveralls, & respiratory protection. Have appropriate equipment available for use in emergencies.

9. PHYSICAL AND CHEMICAL PROPERTIES

Clear liquid.

Specific gravity (20°C)

Solubility in water

Flash point °C (TCC)

Solvent type, %

0.816

Not soluble

<10

Active 15.7

Latent 12.3

Diluent 72.0

10. STABILITY AND REACTIVITY

Conditions to Avoid Stable but corrosive

11. TOXICOLOGICAL INFORMATION

TOXIC: inhalation, ingestion, or skin contact with material may cause severe injury or death.
Contact with molten substance may cause severe burns to skin and eyes.
Effects of contact or inhalation may be delayed.

12. ECOLOGICAL INFORMATION

No ecological problems are expected when the product is handled and used with due care.

13. DISPOSAL CONSIDERATIONS

Disposal Method Product Disposal in accordance with local legal provisions. Disposal recommendations apply to the original material and its container and not to any materials which are a waste by-product of the user's operation. Chemical residues generally count as special waste.
The disposal of the latter is regulated through corresponding laws and regulations. We recommend that you contact the authorities in charge or approved waste disposal companies which will advise you on how to dispose of special waste.

14. TRANSPORT INFORMATION

<u>UN No</u>	1263	<u>Hazchem Code</u>	2x
<u>ERG No</u>	153	<u>EAC</u>	60
<u>IMDG Code</u>	3	<u>IMDG-Packaging Group</u>	11
<u>Marine Pollutant</u>	Yes		
<u>Class</u>	Class: 3	Flammable: II	
<u>Subsidiary Risks</u>	None		
<u>Tremcard Number</u>	****		

15. REGULATORY INFORMATION

Risk Phrases Causes severe burns
Safety Phrases Keep out of reach of children.
In case of contact with eyes, rinse immediately with plenty of water and seek medical advice

16. OTHER INFORMATION

Reason for Alteration: New Product

MANUFACTURERS NOTE

Although the information contained herein is presented in good faith and is to the best of B&R Products knowledge true and accurate, it is made for informational purposes only and without any warranty whatsoever. Due to the special nature of the product and its applications B&R Products does not accept any responsibility or liability whatsoever which may result from the use of this information.

The information contained herein is not to be construed as a license to operate under, or a recommendation to infringe, any existing patents, nor should it be confused with any Governmental or international safety codes.

